

CHOICE BY APPLICATION



Domestic borehole



Heat pumps in buildings



Drinking water



Wastewater plant



Industry



Water recycling



Watering and micro-irrigation



Seawater



AG
automatic filter

- Ideal in the presence of clay or fine sludge.
- Domestic use, protection of heat pumps, watering networks, etc.

- Good turbidity reduction, thanks to our very fine filtration degrees.
- Can be installed on town or private networks.
- ideal to protect reverse osmosis systems.

- Filtration at clarifier-settler outlet.
- Treatment before industrial water network.
- Is part of the RE-USE processes, before UV system.

- Water adduction: treatment of borehole or river water.
- Protection of cooling circuits loaded with dust and metal particles.
- Protection of cooling towers.

- Water containing organic or mineral solids.
- The TSS rate must be low.

- Excellent protection of solenoid valves and micro-irrigation nozzles.
- A rating of 80 to 100 microns is usually sufficient.
- On borehole or surface water.

- A specific seawater version is available.
- Protection of aquaculture ponds or desalination systems.



AS
automatic filter

- Specifically designed for low-pressure networks
- Protection of plate exchangers on ground water
- Filtration degrees: 80 to 200 μm . 6 μm in case of clay deposits

- Ideal on low-pressure networks.

- Water containing mineral solids.
- The TSS rate must be low.



PRAGO 2
automatic filter

- The most affordable solution among automatic filters.
- Elimination of sand present in water.
- Protection of heat pumps or watering networks.

- Suitable for low water flow rate : maximum 8 m^3/h .

- Good protection of solenoid valves and micro-irrigation nozzles.
- On borehole water only.



XT
filter for effluents

- Recycling of process water loaded with high TSS.
- Gravity operation.
- Low water consumption thanks to the use of compressed air for cleaning.



Stainless steel hydrocyclone

- Simple and efficient solution in the presence of sand.
- Manual purging is required, but rarely.

- Simple and efficient solution in the presence of sand.
- Manual purging is required, but rarely.
- Ultra-robust product made of welded stainless steel.

- Good protection of solenoid valves and micro-irrigation nozzles.
- Operates without electricity.
- Ultra-robust product made of welded stainless steel.